

# 30-Gallon

## Air Compressor/ Generator Combinations

Two Stage — Gasoline



AG2-SH13-30M

*The versatile industrial air compressor and generator combination comes with an abundance of storage capacity. This model features a powerful two-stage compressor and a 4000 watt generator and is durable for the rugged environments.*

#### Compressor Pump:

Splash lubricated | Stainless-steel braided discharge hose | Large canister intake filter | Oil level sight indicator

#### Generator:

Brushless alternator | Total harmonic distortion (THD) less than 6% | 100% copper windings | Comes standard with (2) 120V, 20A and (1) 240V, 20A receptacles

#### Frame:

Powder coated ASME coded 30-gallon receiver tank |  $\frac{3}{16}$ -inch base plate to reduce vibration | 16-gauge powder coated two-piece belt guard

#### Components:

Regulator and two gauges for tank and outlet pressure | Manual drain valves for proper maintenance | 16 $\frac{1}{2}$ -inch fly wheel | Quality pilot valve unloader



# 30-Gallon

## Air Compressor/Generator Combinations – Two Stage – Gasoline

MODEL NUMBER	CFM @ 90 PSI	CFM @ 175 PSI*	MAX. AC OUTPUT	ALTERNATOR WATTAGE		RECEPTACLES	DISPLACEMENT/ENGINE	COMPRESSOR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
				CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD						
AG2-SH13-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	389cc Honda GX390 OHV	Two stage, cast iron	40x24.5x45in.	550 lb.	450 lb.
AG2-SK14-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	429cc Kohler CH440 OHV	Two stage, cast iron	40x24.5x45in.	550 lb.	450 lb.
AG2-SM14-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	420cc Mi-T-M OHV	Two stage, cast iron	40x24.5x45in.	550 lb.	450 lb.

\*Equipped with 150-PSI maximum rated regulator.

### Options:

PART NUMBER	DESCRIPTION	FITS MODELS
AX-0019	Electric start - battery, box and cables not included - For easy starting	AG2-SH13-30M
AX-0063	Lifting hook - For easier portability	All models
AX-0064	Electric start - battery box and cables included, battery not included - For easy starting	AG2-SH13-30M
AX-0068	Idle down - When activated it automatically throttles down engine to conserve fuel, includes electric start - battery not included	AG2-SH13-30M
AX-0070	Battery tray, box and 2-ft. of cables - Attaches to engine side of unit	All models
AX-0071	Electric start - battery, box and cables not included - For easy starting	AG2-SK14-30M
AX-0072	Electric start - battery box and cables included, battery not included - For easy starting	AG2-SK14-30M
AX-0073	Electric start - battery, box and cables not included - For easy starting	AG2-SM14-30M
AX-0074	Electric start - battery box and cables included, battery not included - For easy starting	AG2-SM14-30M
AX-0075	Idle down - When activated it automatically throttles down engine to conserve fuel, includes electric start - battery not included	AG2-SM14-30M
IX-0001	Vibration isolator pads - Isolators protect the unit from vibration during use. Recommended for models mounted in service truck applications	All models
IX-0055	Remote start/choke - 6-ft. wire extension for key switch. You will also need to order electric start option, AX-0019 or idle down option, AX-0068.	AG2-SH13-30M
IX-0059	Remote start/choke - 6-ft. wire extension for key switch, sealed cable. You will also need to order electric start option, AX-0019 or idle down option, AX-0068.	AG2-SH13-30M

### Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
70-0358	Engine oil drain extension - 14-inch flexible drain hose makes oil changes clean and easy	All models
AW-6000-1002	Equipment cover - Keeps your equipment clean, dry and looking like new	All models



NEMA 5-20R  
125V



NEMA L6-20R  
240V



AG2-SH13-30M with electric start option, AX-0019

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).