

Aluminum Series

Dealer Cold Water Pressure Washers



This powerful electric pressure washer series is ideal for removing dirt, mud, mold and mildew from almost any surface. Contractors love the lightweight portable model because it is easy to move from one job to the next. This series also offers convenient hand carry and stationary models.

Pump:

Direct drive triplex piston General pump with ceramic plungers | External bypass system allows more water into the system to protect from heat build-up | Stainless-steel and brass trapping unloader

Motor:

Low speed 1750 RPM

Frame (Portable models):

Lightweight, corrosion-resistant aluminum frame and base plate with 1½-inch tube handles $\,$ 13-inch flat-free tires (10-inch on DC-1502-A0E1G)

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° | External downstream detergent injector with detergent nozzle | 50-foot x %-inch non-marking high pressure hose (25-foot on DC-1502 models) | 36-inch lance with rubber grip (48-inch on DC-3005-A0E2G) | Professional-grade insulated "easy pull" trigger gun with safety lock-off



Aluminum Series

Cold Water - Electric - Hand Carry/Portable/Stationary - Direct Drive

Hand Carry Model							
MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-1502-H0E1G	1500	2.0	2.0 HP, 120V, 1Ø, 18.8A	NEMA 5-20P	25x11x14in.	125 lb.	90 lb.
Portable Models							
MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-1502-A0E1G	1500	2.0	2.0 HP, 120V, 1Ø, 18.8A	NEMA 5-20P	40 0,00 E,04 7in	10116	07 11-
	1000	2.0	2.U TP, 12UV, 1W, 10.0A	NEIVIA 3-ZUP	42.9x20.5x24.7in.	104 lb.	87 lb.
DC-2503-A0E2G	2500	3.2	6.0 HP, 230V, 1Ø, 24.1A	NEMA 6-30P	42.9x20.5x24.7m. 46.4x23.8x24.6in.	225 lb.	87 lb. 162 lb.
DC-2503-A0E2G DC-3004-A0E2G							
	2500	3.2	6.0 HP, 230V, 1Ø, 24.1A	NEMA 6-30P	46.4x23.8x24.6in.	225 lb.	162 lb.

Stationary Models							
MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-1502-A0E1G-W*	1500	2.0	2.0 HP, 120V, 1Ø, 18.8A	NEMA 5-20P	24.5x10.8x12.2in.	108 lb.	73 lb.
DC-2503-A0E2G-W*	2500	3.2	6.0 HP, 230V, 1Ø, 24.1A	NEMA 6-30P	29.1x13.5x17.8in.	181 lb.	142 lb.
DC-3004-A0E2G-W*	3000	3.9	8.0 HP, 230V, 1Ø, 34.5A	NEMA 6-50P	30.6x13.7x18.9in.	214 lb.	175 lb.

^{*}Does not ship with handles or wheels, designed for wall mount applications.

Options:

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0005	36-in. insulated dual lance - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	DC-3005-A0E2G
CX-0030	50-ft. x 3/8-in. non-marking high pressure hose - For when you need extra hose for added mobility	DC-1502-H0E1G, DC-1502-A0E1G, DC-1502-A0E1G-W
CX-0104	Wall mount kit - Provides a permanent location for your pressure washer in a shop or facility	DC-1502-A0E1G-W
CX-0105	Wall mount kit - Provides a permanent location for your pressure washer in a shop or facility	DC-2503-A0E2G-W & DC-3004-A0E2G-W

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
18-0370	Rotating nozzle with lance - Increase your cleaning power and decrease your cleaning time, 2400-PSI rated, 1.25mm, 36-inch lance	DC-1502-H0E1G
50-0161	High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up	DC-1502-H0E1G & DC-3005-A0E2G
851-0338	50-ft. x ³ /s-in. non-marking high pressure hose - For when you need extra hose for added mobility	DC-3005-A0E2G
AW-8400-0021	Low pressure detergent injector - Allows the user to apply the recommended detergents	DC-3005-A0E2G



NEMA 5-20P, 20-amp plug



NEMA 6-30P, 30-amp plug



NEMA 6-50P, 50-amp plug



DC-1502-A0E1G-W (stationary) shown with wall mount kit option, CX-0104



DC-1502-H0E1G (hand carry)