

### HDD Series — Direct Drive



HDD-3504-0H6A shown with wheel kit option, AW-5740-0014

*Perfect for agriculture and construction applications where mobility is a must, these compact skids are extremely portable and can fit through a 30-inch doorway. The versatility of this series makes it a popular choice for several industries.*

**Pump:**

Direct drive triplex piston AR pump with ceramic plungers | Low pressure detergent injector

**Engine:**

Performance-proven gasoline engine

**Frame:**

Powder coated steel square tube skid frame | Stainless-steel removable front panel | Optional wheel kit with locking tire brake, four tires and solid steel threaded axles

**Components:**

Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil | 12V Beckett burner – no need for a generator – battery not included | No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel) | Adjustable thermostat

**Miscellaneous:**

Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

**Unit Includes:**

Quick connect nozzles - 0°, 15°, 25° and 40° | 50-foot x 3/8-inch high pressure hose | Adjustable pressure insulated dual lance | Professional-grade insulated trigger gun with safety lock-off



# Skid Gasoline

## Hot Water – HDD Series – Direct Drive

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	ENGINE FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU per hour	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
HDD-3504-0H6A	3500	3.3	389cc Honda GX390 OHV	1.7 gallons	10.0 gallons	2.45 gph	343,000	53.5x28.75x42in.	652 lb.	533 lb.
HDD-3804-0V6A	3800	3.8	480cc Vanguard OHV	10.0 gallons	10.0 gallons	2.45 gph	343,000	53.5x28.75x42in.	677 lb.	558 lb.

### Options:

PART NUMBER	DESCRIPTION	FITS MODELS
HX-0156	Hour meter - Displays the number of hours unit has been in operation	All models
HX-0172	250°F steam - Increases outlet temperature to 250°F, #3 nozzle	All models
HX-0221	High pressure chemical (trapping unloader) - Adjustable high pressure chemical, includes float tank	All models
HX-0222	Panel engine key switch - Moves engine key switch from engine to front panel	HDD-3804-0V6A
HX-0225	Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas	All models
HX-0226	Three-way ball valve - Allows the pressure washer to be operated from garden hose, float tank or trailer supply by adjusting ball lever valve	All models

### Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
50-0170	Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models
850-0324	Gasket (for 50-0170) - Seals between 50-0170 stack adapter and boiler housing	All models
AW-5740-0014	Wheel kit - 4 rubber wheels allows unit to become portable	All models
AW-5740-0015	Caster wheel kit - Includes 2 caster wheels and 2 rubber wheels for easier movement on flat surfaces	All models
AW-6000-1007	Hot water skid equipment cover - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover	All models



HDD-3504-0H6A shown with wheel kit option, AW-5740-0014

**⚠ WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).