

Stationary Oil-Fired

Dealer Hot Water Pressure Washers

HEO Series — Belt Drive



HEO-3004-0E3G shown with fuel tanks option, HX-0218

Designed as a stationary unit with removable side panels, this efficient hot water pressure washer is the perfect solution if you are looking for a wash bay system. The powder coated steel frame makes it extremely durable under tough conditions.

Pump:

Belt drive triplex piston General pump with ceramic plungers | Thermal relief valve | Adjustable high pressure detergent injector

Motor:

Open drip-proof electric motor with manual thermal overload protection

Frame:

Powder coated steel frame and removable side panels

Components:

1/2-inch schedule 80 pipe coil with 5-pancake heat exchanger | 10-inch draft diverter | On/Off burner, pump and motor switches | Pressure switch and over-pressure safety controls | 24V control system | Polyethylene float tank (4-gallon with in-line screen filter) | Adjustable thermostat

Miscellaneous:

Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F (250°F/121°C outlet temperature with steam option) | Designed to run on an existing fuel tank (Optional fuel tanks available)

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° and fixed detergent nozzle | 50-foot x 3/8-inch steel wire-braided high pressure hose | Adjustable pressure insulated dual lance | Professional-grade insulated trigger gun with safety lock-off



Stationary Oil-Fired

Hot Water – HEO Series – Belt Drive

| MODEL NUMBER | PSI | GPM | HORSEPOWER/MOTOR | BTU per hour | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|---------------|------|-----|--------------------------|--------------|--------------------|----------|---------|
| HEO-2004-0E2G | 2000 | 4.2 | 6.0 HP, 230V, 1Ø, 27.1A | 386,400 | 56.5x29x49.75in. | 844 lb. | 724 lb. |
| HEO-2004-0E3G | 2000 | 4.2 | 6.0 HP, 230V, 3Ø, 17.6A | 386,400 | 56.5x29x49.75in. | 844 lb. | 724 lb. |
| HEG-2004-0E4G | 2000 | 4.2 | 6.0 HP, 460V, 3Ø, 8.8A | 386,400 | 56.5x29x49.75in. | 844 lb. | 724 lb. |
| HEG-2004-0E8G | 2000 | 4.2 | 6.0 HP, 208V, 1Ø, 29.8A | 386,400 | 56.5x29x49.75in. | 844 lb. | 724 lb. |
| HEG-2004-0E9G | 2000 | 4.2 | 6.0 HP, 208V, 3Ø, 20.1A | 386,400 | 56.5x29x49.75in. | 844 lb. | 724 lb. |
| HEG-3004-0E2G | 3000 | 3.9 | 8.0 HP, 230V, 1Ø, 38.6A | 343,000 | 56.5x29x49.75in. | 878 lb. | 758 lb. |
| HEG-3004-0E3G | 3000 | 3.9 | 8.0 HP, 230V, 3Ø, 21.6A | 343,000 | 56.5x29x49.75in. | 878 lb. | 758 lb. |
| HEG-3004-0E4G | 3000 | 3.9 | 8.0 HP, 460V, 3Ø, 10.8A | 343,000 | 56.5x29x49.75in. | 878 lb. | 758 lb. |
| HEG-3004-0E8G | 3000 | 3.9 | 8.0 HP, 208V, 1Ø, 42.1A | 343,000 | 56.5x29x49.75in. | 878 lb. | 758 lb. |
| HEG-3004-0E9G | 3000 | 3.9 | 8.0 HP, 208V, 3Ø, 24.6A | 343,000 | 56.5x29x49.75in. | 878 lb. | 758 lb. |
| HEG-3005-0E2G | 3000 | 4.8 | 10.0 HP, 230V, 1Ø, 45.6A | 428,400 | 56.5x29x49.75in. | 878 lb. | 758 lb. |
| HEG-3005-0E3G | 3000 | 4.8 | 10.0 HP, 230V, 3Ø, 26.6A | 428,400 | 56.5x29x49.75in. | 878 lb. | 758 lb. |
| HEG-3005-0E4G | 3000 | 4.8 | 10.0 HP, 460V, 3Ø, 13.3A | 428,400 | 56.5x29x49.75in. | 878 lb. | 758 lb. |
| HEG-3005-0E8G | 3000 | 4.8 | 10.0 HP, 208V, 1Ø, 50.3A | 428,400 | 56.5x29x49.75in. | 878 lb. | 758 lb. |
| HEG-3005-0E9G | 3000 | 4.8 | 10.0 HP, 208V, 3Ø, 30.6A | 428,400 | 56.5x29x49.75in. | 878 lb. | 758 lb. |

Options:

| PART NUMBER | DESCRIPTION | FITS MODELS |
|-------------|---|----------------------------|
| HX-0104 | K7 unloader; flow activated (auto start/stop N/A) - Converts pressure trapping unloader system to flow actuated K7 unloader | HEO-3004 models |
| HX-0106 | Hour meter - Displays the number of hours unit has been in operation | All models |
| HX-0107* | Time delay shutdown - Timer will shut unit off automatically when trigger gun is released and timer reaches setting | All models |
| HX-0108* | Remote station (auto start/stop N/A) - Adds control box which may be mounted away from unit to control on/off, burner and soap injection | All models |
| HX-0110 | Additional remotes (up to 3) - Additional remotes that may be added to the unit after the first remote is installed | All models |
| HX-0111 | Auto start/stop - When trigger gun is released timer will turn unit off; when trigger gun is pulled, unit will restart | All models |
| HX-0112 | K7 unloader; flow activated (auto start/stop N/A) - Converts pressure trapping unloader system to flow actuated K7 unloader | HEO-2004 & HEO-3005 models |
| HX-0114 | Dual gun - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure | HEO-3005 models |
| HX-0115 | Stainless-steel access panels - Converts powder coated painted access panels to stainless-steel material | All models |
| HX-0116 | Stainless-steel coil wrap - Converts powder coated painted coil wrap to stainless-steel material | All models |
| HX-0117 | Painted box kit - Adds painted side and end panels | All models |
| HX-0118 | Painted and stainless-steel box kit - Adds stainless-steel side panels and painted end panels | All models |
| HX-0120 | 250°F steam - Steam option adjusts unloader valve counter-clockwise increasing outlet temperature to 250°F while lowering system pressure | HEO-2004 models |
| HX-0121 | 250°F steam - Steam option adjusts unloader valve counter-clockwise increasing outlet temperature to 250°F while lowering system pressure | HEO-3004 models |
| HX-0122 | 250°F steam - Steam option adjusts unloader valve counter-clockwise increasing outlet temperature to 250°F while lowering system pressure | HEO-3005 models |
| HX-0124 | Auto start/stop and first remote - When trigger gun is released timer will turn unit off; when trigger gun is pulled, unit will restart; adds control box which may be mounted away from unit to control on/off, burner and soap injection | All models |
| HX-0216 | Elevated float tank, 4.0 GPM - Float tank is located at the back of the unit | HEO-2004 & HEO-3004 models |
| HX-0217 | Elevated float tank, 5.0 GPM - Float tank is located at the back of the unit | HEO-3005 models |
| HX-0218^ | (2) 10-gallon fuel tanks - Adds 20-gallon fuel capacity to unit versus hose hook-up to fuel supply | All models |
| HX-0223* | Time delay shutdown and first remote - Timer will shut off automatically when trigger gun is released and timer reaches setting; adds control box which may be mounted away from unit to control on/off, burner and soap injection | All models |

*You cannot order HX-0107 and HX-0108 together, you will need to order HX-0223 instead. See photo of HX-0108 below.

^ You must also order option HX-0216 or HX-0217 when ordering HX-0218.



***HX-0108
Optional
Remote Station**



HEO-3004-0E3G shown with panels removed

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.