

HHM Series — Diesel/Oil-Heated



HHM-3506-0E10

This heater module easily converts your cold water pressure washer into a hot water unit whenever you need it. Featuring a powder coated steel frame assembly and several fuel burner options to fit your needs.

Frame:

Wrinkle-finish powder coated steel frame assembly | Stainless-steel coil wrap |
13-inch flat-free tires

Components:

No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel) |
Horizontal schedule 80 pipe coil heat exchanger | Adjustable thermostat |
35-foot power cord with GFCI

Miscellaneous:

250°F maximum outlet temperature (150°F temperature rise at 4.0-GPM)

Unit Includes:

12-foot x 3/4-inch jumper hose to hook up to existing pressure washer



Heater Module

Hot Water – HHM Series – Diesel/Oil-Heated

MODEL NUMBER	PSI	GPM	ELECTRICAL VOLTAGE/PHASE/AMP	BURNER FUEL CONSUMPTION	DIESEL BTU per hour	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
HHM-3506-0E10	3500	6.0	115V, 1Ø, 3.2A	2.76 gph	386,400	56.5x30x41.5in.	543 lb.	423 lb.

Option:

PART NUMBER	DESCRIPTION	FITS MODEL
HX-0171	Skid feet - Stationary applications	HHM-3506-0E10

Accessories:

PART NUMBER	DESCRIPTION	FITS MODEL
50-0170	Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port	HHM-3506-0E10
850-0324	Gasket (for 50-0170) - Seals between 50-0170 stack adapter and boiler housing	HHM-3506-0E10



GFCI
15-amp plug



HHM-3506-0E10 with DC-3504-A0H6G

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.