

20-Gallon

Industrial Single Stage — Gasoline

With the 20-gallon single stage air compressor, contractors can power a variety of air tools, to get the job done right, every time.



AM1-PH65-20M

COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

FRAME

- Powder coated ASME receiver tank
- $\frac{3}{16}$ -inch base plate to reduce vibration
- Powder coated two-piece belt guard
- 10-inch flat-free tires

COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- Manual drain valve for proper maintenance
- 12-inch fly wheel
- Quality pilot valve unloader
- Start/stop control set at 95 to 125-PSI

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- ASME Boiler and Pressure Vessel Code – UM

MODEL NUMBER	CFM @ PSI	DISPLACEMENT/ENGINE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PH65-20M	13.9 @ 90	196cc Honda GX200 OHV	Pneumatic	37x23.5x33in.	272 lb.	212 lb.
AM1-PM07-20M	13.9 @ 90	212cc Mi-T-M OHV	Cable throttle	37x23.5x33in.	272 lb.	212 lb.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
7-0228A18	Rear lifting handle – Allows the unit to be lifted from both ends	All models
70-0357	Engine oil drain extension – 14-inch flexible drain hose makes oil changes clean and easy	All models
AW-6000-1002	Equipment cover – Keeps your equipment clean, dry and looking like new	All models

OPTIONS: *Options must be ordered with unit and cannot be added later.*

PART NUMBER	DESCRIPTION	FITS MODELS
AX-0003	Manual drain/regulator/metal bowl – Drains moisture from air system	All models
AX-0027	Stationary kit – Converts the portable model to a stationary model, removes the tires and handle, adds a stationary leg	All models



 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.