

## 20-Gallon

### Industrial Two Stage — Gasoline

Remote jobsites require dependable power, and the two-stage, 20 gallon air compressors deliver reliable performance.

#### COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

#### FRAME

- Powder coated ASME receiver tank
- 3/16-inch base plate to reduce vibration
- Powder coated two-piece belt guard
- 13-inch flat-free tires (Portable models)

#### COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- Manual drain valve for proper maintenance
- 16½-inch fly wheel
- Quality pilot valve unloader
- Start/stop control set at 145 to 175-PSI

#### LIMITED WARRANTY

- 3 year engine

#### CERTIFICATION

- ASME Boiler and Pressure Vessel Code – UM



AM2-SH09-20ME

#### PORTABLE MODELS

| MODEL NUMBER   | CFM @ PSI* | DISPLACEMENT/ENGINE   | ENGINE IDLE CONTROL | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|----------------|------------|-----------------------|---------------------|--------------------|----------|---------|
| AM2-PH09-20M   | 17.2 @ 175 | 270cc Honda GX270 OHV | Pneumatic           | 46x26x39.5in.      | 356 lb.  | 306 lb. |
| AM2-PH09-20ME^ | 17.2 @ 175 | 270cc Honda GX270 OHV | Pneumatic           | 46x26x39.5in.      | 363 lb.  | 313 lb. |
| AM2-PM09-20M   | 17.2 @ 175 | 300cc Mi-T-M OHV      | Pneumatic           | 46x26x39.5in.      | 356 lb.  | 306 lb. |
| AM2-PM09-20ME^ | 17.2 @ 175 | 300cc Mi-T-M OHV      | Pneumatic           | 46x26x39.5in.      | 363 lb.  | 313 lb. |

#### STATIONARY MODELS

| MODEL NUMBER   | CFM @ PSI* | DISPLACEMENT/ENGINE   | ENGINE IDLE CONTROL | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|----------------|------------|-----------------------|---------------------|--------------------|----------|---------|
| AM2-SH09-20M   | 17.2 @ 175 | 270cc Honda GX270 OHV | Pneumatic           | 37x18x38in.        | 356 lb.  | 306 lb. |
| AM2-SH09-20ME^ | 17.2 @ 175 | 270cc Honda GX270 OHV | Pneumatic           | 37x18x38in.        | 363 lb.  | 313 lb. |
| AM2-SM09-20M   | 17.2 @ 175 | 300cc Mi-T-M OHV      | Pneumatic           | 37x18x38in.        | 356 lb.  | 306 lb. |
| AM2-SM09-20ME^ | 17.2 @ 175 | 300cc Mi-T-M OHV      | Pneumatic           | 37x18x38in.        | 363 lb.  | 313 lb. |

\*Equipped with 150-PSI maximum rated regulator.

^Equipped with electric start – battery, box and cables not included.

# 20-Gallon

## Air Compressors – Industrial Two Stage – Gasoline

### ACCESSORIES:

| PART NUMBER  | DESCRIPTION                                                                                                                           | FITS MODELS       |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| 854-0093     | Service truck mount kit – Includes four rubber isolators to reduce wear. Recommended for models mounted in service truck applications | Stationary models |
| AW-6000-1002 | Equipment cover – Keeps your equipment clean, dry and looking like new                                                                | All models        |

### OPTIONS: *Options must be ordered with unit and cannot be added later.*

| PART NUMBER | DESCRIPTION                                                                       | FITS MODELS                      |
|-------------|-----------------------------------------------------------------------------------|----------------------------------|
| AX-0003     | Manual drain/regulator/metal bowl – Drains moisture from air system               | All models                       |
| AX-0017     | Battery, battery tray, box and 2-foot of cables – Attaches to engine side on unit | Electric start models            |
| AX-0077     | Battery tray, box and 2-foot of cables – Attaches to engine side of unit          | Electric start models            |
| AX-0101     | Remote start/choke, sealed cable – 7-foot wire extension for key switch           | AM2-PH09-20ME &<br>AM2-SH09-20ME |
| AX-0105     | Remote start/choke, sealed cable – 7-foot wire extension for key switch           | AM2-PM09-20ME &<br>AM2-SM09-20ME |



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).