

# 30-Gallon **Base-Mount**

## Industrial Two Stage - Gasoline

These durable 30-gallon and base-mount air compressors are designed and built to deliver every time.

#### COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- · Oil level sight indicator

#### FRAME

- Powder coated ASME receiver tank (Tank-mount models)
- 3/16-inch base plate to reduce vibration
- Powder coated two-piece belt guard
- Removable base plate offers flexible installation



#### COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- Manual drain valve for proper maintenance
- 161/2-inch fly wheel
- Quality pilot valve unloader
- · Start/stop control set at 145 to 175-PSI

#### LIMITED WARRANTY

· 3 year engine

#### CERTIFICATION

ASME Boiler and Pressure Vessel Code – UM

### TANK-MOUNT MODELS

| MODEL NUMBER   | CFM @ PSI* | DISPLACEMENT/ENGINE   | TANK SIZE | ENGINE IDLE CONTROL | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|----------------|------------|-----------------------|-----------|---------------------|--------------------|----------|---------|
| AM2-SH09-30M   | 17.2 @ 175 | 270cc Honda GX270 OHV | 30-gallon | Pneumatic           | 40.5x17.5x44.5in.  | 446 lb.  | 376 lb. |
| AM2-SH09-30ME^ | 17.2 @ 175 | 270cc Honda GX270 OHV | 30-gallon | Pneumatic           | 40.5x17.5x44.5in.  | 460 lb.  | 390 lb. |
| AM2-SM09-30M   | 17.2 @ 175 | 300cc Mi-T-M OHV      | 30-gallon | Pneumatic           | 40.5x17.5x44.5in.  | 434 lb.  | 364 lb. |
| AM2-SM09-30ME^ | 17.2 @ 175 | 300cc Mi-T-M OHV      | 30-gallon | Pneumatic           | 40.5x17.5x44.5in.  | 449 lb.  | 379 lb. |

#### BASE-MOUNT MODEL

| MODEL NUMBE  | R CFM @ PSI* | DISPLACEMENT/ENGINE   | TANK SIZE  | ENGINE IDLE CONTROL | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|--------------|--------------|-----------------------|------------|---------------------|--------------------|----------|---------|
| AM2-SH09-B^# | 17.2 @ 175   | 270cc Honda GX270 OHV | Base-mount | Pneumatic           | 36.5x21x32in.      | 379 lb.  | 309 lb. |
| AM2-SM09-B^# | 17.2 @ 175   | 300cc Mi-T-M OHV      | Base-mount | Pneumatic           | 36.5x21x32in.      | 379 lb.  | 309 lb. |

\*Equipped with 150-PSI maximum rated regulator.

^Equipped with electric start – battery, box and cables not included. #Receiver tank required.

# **30-Gallon and Base-Mount**

Air Compressors - Industrial Two Stage - Gasoline

| ACCESSORIE   | S:  |                       |  |
|--------------|---|-----------------------|--|
| PART NUMBER  | DESCRIPTION   | FITS MODELS           |  |
| 854-0093     | Service truck mount kit – Includes four rubber isolators to reduce wear. Recommended for models mounted in service truck applications | Tank-mount models     |  |
| AW-6000-1002 | Equipment cover – Keeps your equipment clean, dry and looking like new  | All models            |  |
| OPTIONS: Opt | ions must be ordered with unit and cannot be added later.   |                       |  |
| PART NUMBER  | DESCRIPTION   | FITS MODELS           |  |
| AX-0003      | Manual drain/regulator/metal bowl – Drains moisture from air system   | Tank-mount models     |  |
| AX-0017      | Battery, battery tray, box and 2-foot of cables – Attaches to engine side of unit   | Electric start models |  |
| AX-0077      | Battery tray, box and 2-foot of cables – Attaches to engine side of unit  | Electric start models |  |
| AX-0101      | Remote start/choke, sealed cable – 7-foot wire extension for key switch   | AM2-SH09-30ME         |  |
| AX-0103      | Remote start/choke, sealed cable – 7-foot wire extension for key switch   | AM2-SH09-B            |  |
| AX-0104      | Remote start/choke, sealed cable – 7-foot wire extension for key switch   | AM2-SM09-B            |  |
| AX-0105      | Remote start/choke, sealed cable – 7-foot wire extension for key switch   | AM2-SM09-30MF         |  |



