

30-Gallon

Industrial Two Stage — Gasoline

These air compressor generator combinations are perfect for remodelers, contractors and professionals. With 15.7 CFM and up to 4000 watts, they deliver premium power every time.



AG2-SH13-30ME

COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

GENERATOR

- Brushless alternator
- Total harmonic distortion (THD) less than 6%
- 100% copper windings
- (2) NEMA 5-20R 120V, 20A and
(1) NEMA L6-20R 240V, 20A receptacles

FRAME

- Powder coated ASME receiver tank
- 3/16-inch base plate to reduce vibration
- Powder coated two-piece belt guard
- Removeable base plate offers flexible installation

COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- Manual drain valve for proper maintenance
- 16½-inch fly wheel
- Quality pilot valve unloader

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- ASME Boiler and Pressure Vessel Code – UM

MODEL NUMBER	CFM @ PSI	CFM @ PSI*	MAX. AC OUTPUT	ALTERNATOR WATTAGE		DISPLACEMENT/ENGINE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
				CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD				
AG2-SH13-30M	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	389cc Honda GX390 OHV ⁺	40x24.5x45in.	550 lb.	450 lb.
AG2-SH13-30ME [^]	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	389cc Honda GX390 OHV ⁺	40x24.5x45in.	557 lb.	457 lb.
AG2-SK14-30M	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	429cc Kohler CH440 OHV ⁺	40x24.5x45in.	550 lb.	450 lb.
AG2-SK14-30ME [^]	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	429cc Kohler CH440 OHV ⁺	40x24.5x45in.	557 lb.	457 lb.
AG2-SM14-30M	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	420cc Mi-T-M OHV	40x24.5x45in.	550 lb.	450 lb.
AG2-SM14-30ME [^]	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	420cc Mi-T-M OHV	40x24.5x45in.	557 lb.	457 lb.
AG2-SV14-30M	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	408cc Vanguard OHV ⁺	40x24.5x45in.	550 lb.	450 lb.
AG2-SV14-30ME [^]	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	408cc Vanguard OHV ⁺	40x24.5x45in.	557 lb.	457 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.

**Equipped with 150-PSI maximum rated regulator.*

⁺49 state engine. Not for sale in California.

[^]Equipped with electric start – battery, box and cables not included.

30-Gallon

Air Compressor/Generators – Industrial Two Stage – Gasoline

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
70-0358	Engine oil drain extension – 14-inch flexible drain hose makes oil changes clean and easy	All models
AW-6000-1002	Equipment cover – Keeps your equipment clean, dry and looking like new	All models

OPTIONS: *Options must be ordered with unit and cannot be added later.*

PART NUMBER	DESCRIPTION	FITS MODELS
AX-0016	Battery, battery tray, box and 2-foot of cables – Attaches to engine side of unit	Electric start models
AX-0063	Lifting hook – For easier portability	All models
AX-0068	Idle down – When activated it automatically throttles down engine to conserve fuel	Honda engine models
AX-0070	Battery tray, box and 2-foot of cables – Attaches to engine side of unit	Electric start models
AX-0075	Idle down – When activated it automatically throttles down engine to conserve fuel	Mi-T-M engine models
AX-0083	Idle down – When activated it automatically throttles down engine to conserve fuel	Vanguard engine models
AX-0094	Remote start/choke, sealed cable – 7-foot wire extension for key switch	AG2-SH13-30ME
AX-0095	Remote start/choke, sealed cable – 7-foot wire extension for key switch	AG2-SM14-30ME
AX-0096	Remote start/choke, sealed cable – 7-foot wire extension for key switch	AG2-SV14-30ME
IX-0001	Vibration isolator pads – Isolators protect the unit from vibration during use. Recommended for models mounted in service truck applications.	All models



NEMA 5-20R
125V



NEMA L6-20R
240V



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.