

8-Gallon

Industrial Two Stage — Gasoline

With its wheelbarrow design this unit powers air tools like paint sprayers and pneumatic drills, making it ideal for construction, remodeling and shop projects.



AM2-PK95-08M

COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

FRAME

- Powder coated twin tank receivers
- 3/16-inch base plate to reduce vibration
- Powder coated two-piece belt guard
- 10-inch flat-free tires
- Reinforced frame design (AM2-PH09-08M2)
- Enhanced pilot valve exhaust filter (AM2-PH09-08M2)

COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 16 1/2-inch fly wheel
- Quality pilot valve unloader
- Start/stop control set at 145 to 175-PSI

LIMITED WARRANTY

- 3 year engine

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-PH09-08M	17.2 @ 175	270cc Honda GX270 OHV	Pneumatic	44x26x31in.	330 lb.	260 lb.
AM2-PH09-08ME^	17.2 @ 175	270cc Honda GX270 OHV	Pneumatic	44x26x31in.	337 lb.	267 lb.
AM2-PH09-08M2	17.2 @ 175	270cc Honda GX270 OHV	Pneumatic	44x26x31in.	330 lb.	260 lb.
AM2-PK95-08M	17.2 @ 175	277cc Kohler CH395 OHV	Cable throttle	44x26x31in.	330 lb.	260 lb.
AM2-PM09-08M	17.2 @ 175	300cc Mi-T-M OHV	Pneumatic	44x26x31in.	330 lb.	260 lb.
AM2-PM09-08ME^	17.2 @ 175	300cc Mi-T-M OHV	Pneumatic	44x26x31in.	337 lb.	267 lb.

*Equipped with 150-PSI maximum rated regulator.

^Equipped with electric start – battery, box and cables not included.

ACCESSORY:

PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	Equipment cover – Keeps your equipment clean, dry and looking like new	All models

OPTIONS: Options must be ordered with unit and cannot be added later.

PART NUMBER	DESCRIPTION	FITS MODELS
AX-0003	Manual drain/regulator/metal bowl – Drains moisture from air system	All models
AX-0015	Electric start – battery and cables not included – For easy starting	AM2-PH09-08M2
AX-0084	Stationary option – Converts the portable model to a stationary model, removes the tire and handles	All models except AM2-PH09-08M2
AX-0101	Remote start/choke, sealed cable – 7-foot wire extension for key switch	AM2-PH09-08ME
AX-0102	Remote start/choke, sealed cable; requires option AX-0015 – 7-foot wire extension for key switch	AM2-PH09-08M2
AX-0105	Remote start/choke, sealed cable – 7-foot wire extension for key switch	AM2-PM09-08ME