

Aluminum Series

Gasoline — Belt Drive
Portable

Built to last, this aluminum series provides exceptional performance for proper surface preparation and the removal of muck and grime.



DC-4004-BA0K6G

PUMP

- Belt drive triplex piston pump with ceramic plungers
- Stainless-steel and brass trapping unloader
- External bypass system protects from heat build-up

FRAME

- Corrosion-resistant aluminum frame
- Patented vibration isolation plate
- Two-piece belt guard
- 13-inch tires

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- External downstream detergent injector with detergent nozzle
- 50-foot x 3/8-inch non-marking high pressure hose with quick connects
- Insulated trigger gun

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- ETL Certified – US (Select models, see chart below)

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-3504-BA0H6G*	3500	4.0	389cc Honda GX390 OHV*	General	48in.	46.5x28x27.5in.	215 lb.	165 lb.
DC-3504-BA0K6G*	3500	3.7	429cc Kohler CH440 OHV*	General	48in.	46.5x28x27.5in.	237 lb.	173 lb.
DC-3504-BA0H6A*	3500	3.7	389cc Honda GX390 OHV*	AR	48in.	46.5x28x27.5in.	215 lb.	165 lb.
DC-3504-BA0K6A*	3500	3.7	429cc Kohler CH440 OHV*	AR	48in.	46.5x28x27.5in.	219 lb.	155 lb.
DC-3504-BA0M6A	3500	3.7	420cc Mi-T-M OHV	AR	48in.	46.5x28x27.5in.	215 lb.	165 lb.
DC-4004-BA0H6G*	4000	4.0	389cc Honda GX390 OHV*	General	48in.	46.5x28x27.5in.	223 lb.	159 lb.
DC-4004-BA0K6G*	4000	3.5	429cc Kohler CH440 OHV*	General	48in.	46.5x28x27.5in.	219 lb.	173 lb.
DC-4004-BA0H6A*	4000	3.4	389cc Honda GX390 OHV*	AR	48in.	46.5x28x27.5in.	207 lb.	143 lb.
DC-4004-BA0K6A*	4000	3.4	429cc Kohler CH440 OHV*	AR	48in.	46.5x28x27.5in.	215 lb.	155 lb.
DC-4004-BA0M6A	4000	3.4	420cc Mi-T-M OHV	AR	48in.	46.5x28x27.5in.	215 lb.	165 lb.
DC-4004-BA0H6C*	4000	3.7	389cc Honda GX390 OHV*	CAT	48in.	46.5x28x27.5in.	206 lb.	156 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.

*49 state engine. Not for sale in California. *ETL Certified – US

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector – High pressure water mixes with detergent to clean even the heaviest build-up	All models
851-0338	50-foot x 3/8-inch non-marking hose – For when you need extra hose for added mobility	All models
AW-7510-0035	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 5100-PSI rated, 3.5 orifice	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models