

Portable LP

Belt Drive — DHL Series

The DHL Series is powerful and mobile, making it the perfect choice for various projects.



DH-0703-LP2E1A
(LP tank shown not included)

PUMP

- Belt drive triplex crankshaft pump with solid ceramic pistons
- Factory preset unloader

MOTOR

- Open drip-proof electric motor
- 35-foot power cord with GFCI

FRAME

- Reinforced powder coated cabinet-style steel frame
- 10-inch flat-free tires

COMPONENTS

- LP gas-fired (vapor only) natural draft with aspirating-type burner
- High limit temperature control for added safety
- LP gas regulator
- Hour meter

MISCELLANEOUS

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature 200°F
- Water output temperature is 250°F plus unit operates at 350-PSI in "wet" steam (DH-0703-LP2E1A)

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25°, 40° and detergent nozzle
- 50-foot x 3/8-inch steel wire-braided high pressure hose with quick connects
- 36-inch insulated lance with trigger gun

LIMITED WARRANTY

- 1 year electric motor

CERTIFICATION

- ETL Certified – US and Canada

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	PLUG TYPE	LP GAS BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DH-0703-LP2E1A*	700	2.3	1.5 HP, 120V, 10, 13.2A	AR	NEMA 5-15P	185,000	57.5x35.5x59.5in.	471 lb.	348 lb.
DH-1502-LP2E1A	1500	1.8	2.0 HP, 120V, 10, 18.8A	AR	NEMA 5-20P	185,000	57.5x35.5x59.5in.	505 lb.	382 lb.

*Combination wet steam cleaner/pressure washer.



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug



DH-1502-LP2E1A



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.