

## Portable Electric

### Belt Drive — DHS Series

Blast away greasy residue and tough debris with these heavy-duty pressure washers.



DH-2504-SE0E3G

#### PUMP

- External bypass system protects from heat build-up
- Belt drive triplex piston pump with ceramic plungers
- Factory preset unloader

#### MOTOR

- Totally enclosed fan-cooled electric motor
- 35-foot power cord

#### FRAME

- Reinforced powder coated steel frame with center balanced lift
- 13-inch flat-free tires

#### COMPONENTS

- Energy-efficient top-fired heat exchanger
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)

#### MISCELLANEOUS

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 225°F

#### UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch steel wire-braided high pressure hose with quick connects
- Adjustable pressure insulated dual lance with trigger gun

#### LIMITED WARRANTY

- 1 year electric motor

#### CERTIFICATION

- ETL Certified – US and Canada

| MODEL NUMBER   | PSI  | GPM | HORSEPOWER/MOTOR             | PUMP    | PLUG TYPE    | BURNER FUEL TANK CAPACITY | BURNER FUEL CONSUMPTION | BTU PER HOUR | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|----------------|------|-----|------------------------------|---------|--------------|---------------------------|-------------------------|--------------|--------------------|----------|---------|
| DH-2504-SE0E2G | 2500 | 3.2 | 6.0 HP, 230V, 1Ø, 25.0A      | General | NEMA 6-30P   | 10.0 gallons              | 2.10 gph                | 294,000      | 49.5x28x40.5in.    | 699 lb.  | 569 lb. |
| DH-2504-SE0E3G | 2500 | 3.2 | 6.0 HP, 230-460V, 3Ø, 17.3A  | General | NEMA L15-20P | 10.0 gallons              | 2.10 gph                | 294,000      | 49.5x28x40.5in.    | 688 lb.  | 558 lb. |
| DH-3004-SE0E2G | 3000 | 3.5 | 8.0 HP, 230V, 1Ø, 36.0A      | General | NEMA 6-50P   | 10.0 gallons              | 2.10 gph                | 294,000      | 49.5x28x40.5in.    | 737 lb.  | 607 lb. |
| DH-3004-SE0E3G | 3000 | 3.5 | 8.0 HP, 230-460V, 3Ø, 24.0A  | General | NEMA L15-30P | 10.0 gallons              | 2.10 gph                | 294,000      | 49.5x28x40.5in.    | 732 lb.  | 602 lb. |
| DH-3504-SE0E2G | 3500 | 3.3 | 10.0 HP, 230V, 1Ø, 39.0A     | General | NEMA 6-50P   | 10.0 gallons              | 2.10 gph                | 294,000      | 49.5x28x40.5in.    | 761 lb.  | 631 lb. |
| DH-3504-SE0E3G | 3500 | 3.3 | 10.0 HP, 230-460V, 3Ø, 28.0A | General | NEMA L15-30P | 10.0 gallons              | 2.10 gph                | 294,000      | 49.5x28x40.5in.    | 742 lb.  | 612 lb. |
| DH-4004-SE0E2G | 4000 | 3.5 | 10.0 HP, 230V, 1Ø, 39.0A     | General | NEMA 6-50P   | 10.0 gallons              | 2.10 gph                | 294,000      | 49.5x28x40.5in.    | 761 lb.  | 631 lb. |
| DH-4004-SE0E3G | 4000 | 3.5 | 10.0 HP, 230-460V, 3Ø, 28.0A | General | NEMA L15-30P | 10.0 gallons              | 2.10 gph                | 294,000      | 49.5x28x40.5in.    | 742 lb.  | 612 lb. |

# Portable Electric

## Hot Water – Belt Drive – DHS Series

### ACCESSORY:

| PART NUMBER | DESCRIPTION                                                             | FITS MODELS |
|-------------|-------------------------------------------------------------------------|-------------|
| 850-0433    | 50-foot x ¾-inch hose – For when you need extra hose for added mobility | All models  |

### OPTIONS: Options must be ordered with unit and cannot be added later.

| PART NUMBER | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                              | FITS MODELS                     |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| HX-0070     | Auto start/stop – When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart                                                                                                                                                                                                                                              | All models                      |
| HX-0071*    | Auto start/stop - steam – When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart; reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F                                                                                 | DH-2504 models                  |
| HX-0072*    | Auto start/stop - steam – See HX-0071 for description                                                                                                                                                                                                                                                                                                                    | DH-3004 models                  |
| HX-0073*    | Auto start/stop - steam – See HX-0071 for description                                                                                                                                                                                                                                                                                                                    | DH-3504 & DH-4004 models        |
| HX-0074     | Auto start/stop - CAD cell – When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart; monitors burner for proper ignition                                                                                                                                                                                              | All models                      |
| HX-0075*    | Auto start/stop - steam - CAD cell – When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart; reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F; monitors burner for proper ignition; Includes adjustable thermostat | DH-2504 models                  |
| HX-0076*    | Auto start/stop - steam - CAD cell – See HX-0075 for description                                                                                                                                                                                                                                                                                                         | DH-3004 models                  |
| HX-0077*    | Auto start/stop - steam - CAD cell – See HX-0075 for description                                                                                                                                                                                                                                                                                                         | DH-3504 & DH-4004 models        |
| HX-0085     | 460V on 6.0-HP, 3Ø model – Upgrades 230V, 3Ø model to operate at 460V, 3Ø                                                                                                                                                                                                                                                                                                | DH-2504-SE0E3G                  |
| HX-0086     | 460V on 8.0-HP, 3Ø model – Upgrades 230V, 3Ø model to operate at 460V, 3Ø                                                                                                                                                                                                                                                                                                | DH-3004-SE0E3G                  |
| HX-0087     | 460V on 10.0-HP, 3Ø model – Upgrades 230V, 3Ø model to operate at 460V, 3Ø                                                                                                                                                                                                                                                                                               | DH-3504-SE0E3G & DH-4004-SE0E3G |
| HX-0088     | Skid feet – Stationary applications                                                                                                                                                                                                                                                                                                                                      | All models                      |
| HX-0161     | Hour meter – Displays the number of hour unit has been in operation                                                                                                                                                                                                                                                                                                      | All models                      |
| HX-0294     | Adjustable thermostat – Operator is able to adjust outlet water temperature between 86°-248°F                                                                                                                                                                                                                                                                            | All models                      |
| HX-0312     | 35-foot power cord with GFCI – Replaces the standard 35-foot power cord with a GFCI cord                                                                                                                                                                                                                                                                                 | DH-3004-SE0E2G                  |

\*Includes adjustable thermostat.



NEMA L15-20P,  
20-amp plug



NEMA L15-30P,  
30-amp plug



NEMA 6-30P,  
30-amp plug



NEMA 6-50P,  
50-amp plug



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).