

Heater Module

Diesel/Oil-Heated — HHM Series

The HHM Series heater modules are the perfect addition to a cold water pressure washer. Convert cold water into hot for added cleaning power.



HHM-3506-1E10

FRAME

- Powder coated steel frame
- 13-inch flat-free tires

MISCELLANEOUS

- 250°F maximum outlet temperature (150°F temperature rise at 4.0 GPM)

COMPONENTS

- Horizontal schedule 80 pipe coil heat exchanger
- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)
- Adjustable thermostat
- 35-foot power cord with GFCI

UNIT INCLUDES

- 12-foot x ½-inch jumper hose to hook up to existing pressure washer

CERTIFICATION

- ETL Certified – US and Canada

MODEL NUMBER	PSI RATING	GPM RATING	ELECTRICAL	BURNER FUEL CONSUMPTION	DIESEL BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
HHM-3506-1E10	3500	6.0	115V, 1Ø, 3.2A	2.76 gph	386,400	56.5x30x41.5in.	543 lb.	423 lb.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODEL
50-0170	Stack adapter – Allows 8-inch flue pipe to be installed to boiler exhaust port	HHM-3506-1E10
850-0324	Gasket – Seals between 50-0170 stack adapter and boiler housing	HHM-3506-1E10

OPTION: *Option must be ordered with unit and cannot be added later.*

PART NUMBER	DESCRIPTION	FITS MODEL
HX-0171	Skid feet – Stationary applications	HHM-3506-1E10



GFCI
15-amp plug



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.