

Premium Series

Diesel — Belt Drive Portable

This series uses diesel power to handle cleaning jobs in a variety of industries.



DC-3004-W0K7G

PUMP

- Belt drive triplex piston pump with ceramic plungers
- External bypass system protects from heat build-up
- Factory preset stainless-steel and brass unloader
- Water filter with clear sleeve for screen inspection

ENGINE

- Electric start – battery not included

FRAME

- Powder coated steel frame
- Enclosed belt guard
- 13-inch tires

COMPONENT

- Dual cogged belt drive system

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch non-marking high pressure hose with quick connects
- Insulated trigger gun

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- ETL Certified – US

MODEL NUMBER	PSI	GPM	HORSEPOWER/ENGINE	PUMP	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-3004-W0K7G	3000	3.9	9.1 HP Kohler KD440 OHV with electric start - battery not included	General	36in.	46x28x30in.	321 lb.	245 lb.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODEL
851-0338	50-foot x 3/8-inch non-marking hose – For when you need extra hose for added mobility	DC-3004-W0K7G
AW-7510-0004	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage, 4.0 orifice size	DC-3004-W0K7G
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	DC-3004-W0K7G

OPTIONS: *Options must be ordered with unit and cannot be added later.*

PART NUMBER	DESCRIPTION	FITS MODEL
CX-0005	36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	DC-3004-W0K7G
CX-0054	Roll cage – Designed to protect equipment, comes with a lifting hook, 1 1/4-inch powder coated steel tubing	DC-3004-W0K7G