

Water Transport Trailers

Water Trailer with Semi-Trash Pump

Tame dust, clean parking lots or haul water with these water transport trailers. These units feature a 510-gallon water tank, rear spray, hose hook-ups and more.



MWT-0510-2MMD

TANK

- 510-gallon elliptical low profile $\frac{3}{8}$ -inch thick polyethylene
- 16-inch manhole with 4-inch vent

CENTRAL MANIFOLD

- Easy-to-operate butterfly brass valves

PLUMBING

- $1\frac{1}{2}$ -inch fire hose hook-up with 50-foot x $1\frac{1}{2}$ -inch hose and fog nozzle
- Break-away hydrant fill with 25-foot x $2\frac{1}{2}$ -inch hose
- Dual rear spray heads
- Garden hose connector
- Manifold discharge system
- Water hammer prevention valve

TRAILER

- DOT approved
- 12-inch under-clearance at axle
- 7,000-lb. side-mount crank jack
- Dual leaf spring suspension
- Rubber mounted sealed lights
- Wire storage basket
- Two safety chains with snap hooks
- (4) ST225-75 15-inch tires

SEMI-TRASH PUMP

- 2-inch suction and discharge that handles solids up to $\frac{3}{4}$ -inch diameter
- Heavy-duty powder coated wraparound frame
- Silicon carbide mechanical seals
- Precision molded cast iron impeller and volute for reduced vibration and wear

LIMITED WARRANTY

- 3 year engine

MODEL NUMBER	DISPLACEMENT/ENGINE	PUMP	HITCH	AXLES	BED FRAME	DIMENSIONS (LxWxH)	TRAILER WT. (EMPTY)	TRAILER WT. (LOADED)
MWT-0510-2MHD	196cc Honda GX200 OHV	2in. semi-trash	2in., ball	(2) 3,500 lb. tandem with hydraulic surge brakes	5ft.x8ft.	13.7x6.8x5.8ft.	1,580 lb.	5,900 lb.
MWT-0510-2MMD	212cc Mi-T-M OHV	2in. semi-trash	2in., ball	(2) 3,500 lb. tandem with hydraulic surge brakes	5ft.x8ft.	13.7x6.8x5.8ft.	1,580 lb.	5,900 lb.

OPTIONS: Options must be ordered with unit and cannot be added later.

PART NUMBER	DESCRIPTION	FITS MODELS
TX-0008	Hard suction option – Allows you to draw water from an auxiliary source (pond, water pit, etc.). The fire hose is designed to be used with pressurized water and lays flat for easy storage.	All models without the TX-0024 water bypass option
TX-0010	Adjustable trailer coupler hitch – Replaces the standard 2-inch ball hitch with a 2-inch trailer hitch with pin-style fastener trailer coupler and hinged ball socket	All models
TX-0019	Lunette ring hitch – Replaces the standard 2-inch ball hitch with a 3-inch integrated lunette ring for use with pintle hitches	All models
TX-0024	Water bypass – Allows you to bypass water from the outlet back to the tank. This can be used to reduce outlet pressure and flow for desired application	All models without the TX-0008 hard suction option



 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.